



# iClamshell Card LF

## MECHANICAL DIMENSIONS

|             |                      |
|-------------|----------------------|
| • Length    | 85.80 mm +/- 0.40 mm |
| • Width     | 54.0 mm +/- 0.40 mm  |
| • Thickness | 1.6mm +/- 0.40 mm    |

## COLOUR

- White

## WEIGHT

- 8g typical

## INTEGRATED CIRCUITS (\*OTHERS UPON REQUEST)

|         |       |                |
|---------|-------|----------------|
| • ATMEL | T5577 | 330 BIT R/WOTP |
|---------|-------|----------------|

## OPERATING FREQUENCY

- 125 MHz typical

## OPTIONS

|                         |                           |
|-------------------------|---------------------------|
| • Logo on hard shell    | Insert on lot of 50K pcs  |
| • Print/Laser engraving | Logo, serial number       |
| • Programming           | Initialisation on request |

## OPERATING TEMPERATURE

- -35°C to +50°C

## MATERIAL (HARD SHELL ABS, PVC STICKER ON THE BACK SIDE)

### PVC

|                         |                 |
|-------------------------|-----------------|
| • Operating Temperature | -35°C to +100°C |
|-------------------------|-----------------|

## CHEMICAL RESISTANCE

- Designed for use under normal access control conditionsTechnology

## APPLICATION SPECTRUM

- Access control



© STS Contactless

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.