



iDisc HF

MECHANICAL DIMENSIONS

• Diameter	20/30/50mm +/-0.3 mm
• Thickness	3mm/3mm/3.65mm +/-0.2 mm
• Hole	no hole/5,2mm +/- 0,2mm

MATERIAL

- Polyamide with glass fiber

COLOUR

- Black

WEIGHT

- 1,7g typical, 3,7g typical, 11,2g typical

INTEGRATED CIRCUITS (*OTHERS UPON REQUEST)

- NXP I-Code SLI 1kBIT R/W

OPERATING FREQUENCY

- 14,5 MHz typical +/-0,5MHz

OPTIONS

- Customized embossed logo on lots of 50k

STORAGE TEMPERATURE

- -35°C to +100°C

OPERATING TEMPERATURE

- -35°C to +85°C

SHOCK TEMPERATURE

- -35°C to +100°C (500 times 15 min with transition time of 50s)

PEAK TEMPERATURE

- 150°C (60min) – functional test ok

WATERPROOFNESS

- IP68 (50m, 24h)

CHEMICAL RESISTANCE

- 5% Sodium Chloride – 24h
- 5% Sodium Carbonate – 24h
- 5% Acetic acid – 24h
- Gasoline – 24h
- Hot Oil 150°C – 15mins

APPLICATION SPECTRUM

- Industrial and Logistics (palette, tool, box....)



© STS Contactless
All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.