

Accessory Tag HF

MECHANICAL DIMENSION	S	
Length	45 mm	
• Width	20 mm	
Thickness	3.7 mm	

COLOUR

• Customized (as per request)

WEIGHT

• 3.7 g typical

INTEGRATE	D CIRCUITS (*OTHERS	UPON REQUEST)	
• NXP	Mifare 1K	1k byte R/W	ISO 14443 A
• NXP	Mifare 4K	4k byte R/W	ISO 14443 A
• NXP	Mifare DESFire	4k Crypto R/W	ISO 14443 A
• NXP	Mifare UL	64 byte R/W	ISO 14443 A
• NXP	I-Code SLI	1k bit R/W	ISO 15693
• NXP	Mifare Mini	320 byte R/W	ISO 14443 A
 Infineon 	Mifare NRG	1k byte R/W	ISO 14443 A

Customized design

Initialisation on request

Logo and image can be made Semi-transparent color can be made

OPERATING FREQUENCY

• 13.56 MHz typical

OPTIONS

• Print

Programming

MATERIAL

Epoxy coated

APPLICATION SPECTRUM

Acess control, payment, loyalty, transport and secured identification



© STS Contactless

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.